

As manufacturer we can offer you the following:

Barrier post, traffic bollard, demarcation post
Bumper bollard,

For all information and requests, you can
reach us on: info@i-m-c.be



	Number of bollards per pallet
Ø 101.6	15
Ø 104	15
Ø 154	15
Ø 156	15

This list contains our standard dimensions.
Other dimensions are also possible.

code			weight
------	--	--	--------



Bollard removable Ø 104 x 2 mm Rounded head Stainless steel 304/316 Pole brushed – polished head Locking system with triangle key Seamless finish	Code			
	RP-WNB-104x2x750-rvs304			6.5 kg
	RP-WNB-104x2x750-rvs316			6.5 kg
	RP-WNB-104x2x900-rvs304			7 kg
	RP-WNB-104x2x900-rvs316			7 kg



Bollard removable Ø 101.6 x 3.05 mm Rounded head Stainless steel 304/316 Pole brushed – polished head Locking system with triangle key Seamless finish	Code			
	RP-WNB-101.6x3.05x750-rvs304			8 kg
	RP-WNB-101.6x3.05x750-rvs316			8 kg
	RP-WNB-101.6x3.05x900-rvs304			9 kg
	RP-WNB-101.6x3.05x900-rvs316			9 kg



Bollard removable Ø 154 x 2 mm Rounded head Stainless steel 304/316 Pole brushed – polished head Locking system with triangle key Seamless finish	Code			
	RP-WNB-154x2x750-rvs304			10 kg
	RP-WNB-154x2x750-rvs316			10 kg
	RP-WNB-154x2x900-rvs304			11 kg
	RP-WNB-154x2x900-rvs316			11 kg



Bollard removable Ø 156 x 3 mm Rounded head Stainless steel 304/316 Pole brushed – polished head Locking system with triangle key Seamless finish	Code			
	RP-WNB-156x3x750-rvs304			12 kg
	RP-WNB-156x3x750-rvs316			12 kg
	RP-WNB-156x3x900-rvs304			13.5 kg
	RP-WNB-156x3x900-rvs316			13.5 kg



Ground socket in galvanised steel L:240 x B:240 x H:300 mm	Code		weight
	sokkel		10 kg



Triangle key	Code		weight
	driekantsleutel		0.08 kg



Hexagon key	Code		weight
	zeskantsleutel		0.250 kg

Threaded rod for removable bollard– complete with triangle head or hexagon head		

Locking nut		

Seamless finish

Triangular head



Hexagon head



option

With ring for chain or rope



∅ 101.6	
∅ 104	

option

Reflective tape

Height per band is 55 mm. The tape is placed with an intermediate distance of 55 mm

White



Yellow



red



1 reflective tape



2 reflective tapes



option

Electropolishing

- Greatly improved corrosion resistance
- Great resistance to sticking
- Greatly improved cleanability
- Extremely hygienic and bacteriologically clean surface
- Smoother and denser surface, lower roughness, deburring
- Elimination of the weld discoloration, higher shine
- Low flow resistance and good thermal effect
- Extremely passive and noble surface

Recommended for use on the coast and in environments with acids and salts.

These are finished products. These products are not suitable for any post-treatment.
IMC cannot be held liable for damage due to failure to maintain the products.